


# Aerial Work Platforms

## IWP™ Super Series™

### Specifications



Models	IWP-20S		IWP-25S		IWP-30S	
Measurements	Metric	US	Metric	US	Metric	US
Working height*	8.15 m	26 ft 2 in	9.44 m	30 ft 5 in	11 m	35 ft 6 in
Platform height	6.15 m	20 ft 2 in	7.44 m	24 ft 5 in	9 m	29 ft 6 in
<b>A</b> Horizontal outreach**	66 cm	2 ft 2 in	---	---	---	---
<b>B</b> Height - stowed:						
fully lowered	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in
base raised	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in
<b>C</b> Length	1.52 m	5 ft	1.52 m	5 ft	1.52 m	5 ft
<b>D</b> Width - standard base	81 cm	2 ft 8 in	81 cm	2 ft 8 in	---	---
wide base	---	---	---	---	1.02 m	3 ft 4 in
Corner access***	15 cm	6 in	15 cm	6 in	18 cm	7 in

### Productivity

Lift capacity	159 kg	350 lbs	159 kg	350 lbs	159 kg	350 lbs
Platform Dimensions (l/w/h)						
Standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated narrow	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in
Standard fiberglass**	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in

### Power

AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V

### Sound & Vibration Levels

Sound pressure level (ground workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Sound pressure level (platform workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Vibration	<2.5 m/s <sup>2</sup>	<8 ft 2 in/s <sup>2</sup>	<2.5 m/s <sup>2</sup>	<8 ft 2 in/s <sup>2</sup>	<2.5 m/s <sup>2</sup>	<8 ft 2 in/s <sup>2</sup>

### Weight\*\*\*\*

<b>Standard base</b>						
AC	565 kg	1,245 lbs	585 kg	1,290 lbs	---	---
DC	610 kg	1,345 lbs	630 kg	1,390 lbs	---	---
<b>Standard base with outreach option</b>						
AC	612 kg	1,350 lbs	---	---	---	---
DC	658 kg	1,450 lbs	---	---	---	---
<b>Wide base</b>						
AC	---	---	---	---	649 kg	1,430 lbs
DC	---	---	---	---	694 kg	1,530 lbs

### Standards Compliance

EU Directives: 2006/42/EC - Machinery (harmonized standard EN280:2013); 2004/108/EC (EMC); 2006/95/EC (LVD)

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

\*\* Fiberglass platforms are not available with the outreach option.

\*\*\* Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.

\*\*\*\* Weight will vary depending on options and/or country standards.

### Features

Standard Features	Easily Configured To Meet Your Needs	Options & Accessories
-------------------	--------------------------------------	-----------------------

#### Measurements

##### IWP-20S

- 8.24 m (26 ft 6 in) working height
- 6.24 m (20 ft 6 in) platform height
- 81 cm (2 ft 8 in) standard base width
- Outreach option adds 66 cm (2 ft 2 in) of horizontal reach
- Up to 159 kg (350 lbs) lift capacity

##### IWP-25S

- 9.44 m (30 ft 5 in) working height
- 7.44 m (24 ft 5 in) platform height
- 81 cm (2 ft 8 in) standard base width
- Up to 159 kg (350 lbs) lift capacity

##### IWP-30S

- 11 m (35 ft 6 in) working height
- 9 m (29 ft 6 in) platform height
- 1.02 m (3 ft 4 in) wide base width
- Up to 159 kg (350 lbs) lift capacity

#### Productivity

- Auxiliary platform lowering
- Most rigid mast in the industry
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Built-in level sensing with interlocks

#### Platform Options

- Sliding mid-rail platform (standard)
- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform (not available with outreach)

#### Power Options

- AC power 85V / 50-60 Hz
- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power with worldwide automatic "smart" charging system (12V / 110V / 230V / 50-60 Hz)

#### Base Options

- Standard base (IWP-20S and 25S only)
- Wide base (IWP-30S only)

#### Productivity

- Outreach option (IWP-20S only)<sup>(3)(4)</sup>
- Power to platform (plug, socket and ground fault interrupt leakage on request)
- Operational warning light and descent alarm package
- Tool tray<sup>(1)</sup>
- Fluorescent tube caddy<sup>(1)</sup>
- Platform locating laser light<sup>(1)</sup>

#### Power

- Power wheel assist with dual battery package<sup>(2) (3)</sup>
- Dual battery package<sup>(3)</sup>



<sup>(1)</sup> Available on selected models only. See your Genie representative for further information.

<sup>(2)</sup> Adds 32 cm (12.5 in) to unit length and 129 kg (285 lbs) to unit weight.

<sup>(3)</sup> Factory-fit option only.

<sup>(4)</sup> The outreach option reduces the lift capacity to 136 kg (300 lb)

### United Kingdom

The Maltings, Wharf Road, Grantham NG31 6BH, T: +44 800 988 3739 (toll free), Fax +44 (0)1476 584334, Email AWP-InfoEurope@terex.com  
Visit [www.genielift.co.uk/locations](http://www.genielift.co.uk/locations) to view our global locations list.

### Worldwide Manufacturing And Distribution

Australia · Brazil · Caribbean · Central America · China · France · Germany · Italy · Japan · Korea · Mexico · Russia · Southeast Asia · Spain · Sweden · United Arab Emirates · United Kingdom · United States

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2017 Terex Corporation.

